

BURDA PRAHA

Luxembourg Plaza, Přemyslovská 2845/43, 130 00 Praha 3; Tel.: +420 221 589 355, Fax: +420 221 589 331

BURDA PRAHA


Luxembourg Plaza, Přemyslovská 2845/43, 130 00 Praha 3; Tel.: +420 221 589 355, Fax: +420 221 589 331

DIGITAL DATA RECEPTION FOR ADVERTISEMENT PURPOSES


ADVERTISEMENT DATA ARE ACCEPTED IN THE ELECTRONIC FORM ONLY AND MUST COMPLY TO THE FOLLOWING SPECIFICATIONS

SINGLE PAGE

trim size: 216x272, type area: 200x258




HALF-PAGE (WIDTH)




trim size 216x132
type area 200x126

HALF-PAGE (HEIGHT)




trim size 105x272
type area 100x258

1/3 PAGE (HEIGHT)




trim size 70x272
type area 65x258

1/3 PAGE (WIDTH)




trim size 200x84
type area 216x90

1/4 PAGE (NORMAL)




trim size 105x132
type area 100x126

1/6 PAGE



type area 100x84

JUNIOR PAGE



trim size 132x216
type area 126x200

1/ PROOF-SHEETS

A certificated digital proof-sheet in accordance with ISO 12647-2 (ISO Coated v. 2) standard, specifically - for covers with FOGRA 39 (ISO coated_v2_eci) Mediawedge V3.0a and for inside pages with FOGRA 46 Mediawedge V3.0a, must be supplied together with the data as a binding color sample. Should the previously mentioned proof-sheet not be supplied, the client's entitlement to claim refund due to discrepancy in quality of print or variation in color will expire immediately.

2/ RECEPTION OF DATA

Data delivery

By e-mail to inzeraty@burda.cz (please specify magazine name, issue, issue date and client name in the subject) or on CD.

Please send the proof-sheet to *BURDA Praha, Luxembourg Plaza, Přemyslovská 2845/43, 130 00 Praha 3, Ad Coordination Dept.*

3/ TECHNICAL SPECIFICATION OF DELIVERED DATA

- A composite print-ready PDF must be in version 1.3.
- The PDF document must not contain any of the following: primary colors; RGB, LAB or ICC profiles, OPI, negative text smaller than 9pt.; or hairlines and text smaller than 5pt. Hairline width in the document will be automatically converted to 0.3pt and primary colors will be converted into the CMYK color mode without further notice.
- We only accept data produced using Adobe Distiller, InDesign 3 or 4 or a special standardized software intended for the production of print-ready PDFs
- We recommend to convert all texts into curves. If texts are not converted into curves, all fonts must be correctly embedded into the PDF.
- An advertisement must occupy only one page, have a proper size, be centered, and contain crop marks and 5 mm bleeds along all sides (with the exception of data delivered for special V-gate or Z-gate advertisement pages, to which special specifications apply). MediaBox must be 20mm larger than a TrimBox PDF.
- Any objects which are not located in the bleed area must be placed at least 6 mm from the net format of the advertisement (a security zone – due to magazine binding and crop technical tolerance of +/- 2 mm).
- Files with resolution of less than 300 dpi are regarded as previews and will be returned.
- An advertisement smaller than single page, delivered like type area, must be prepared without bleed.
- No CoreDraw data are accepted!
- In the event that the publisher requires an adjustment of supplied advertising data, the client is obliged to provide the requested data without billing of any additional costs which may be incurred by the client.